

# SAFETY DATA SHEET

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

**N® Sodium Silicate Solution Product Name** 

Alternative names Sodium silicate solution

(2.6 < MR < = 3.2)

CAS No. 1344-09-8 EINECS No. 215-687-4

Distributed by: **Rocky Mountain Reagents** 4621 Technology Drive, Golden, CO 80403

> ph: (303) 762-0800 fax: (303) 762-1240 Product #: S1136

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified use(s) General purpose industrial chemical for use in a wide range of

applications.

Binding agent : Corrosion inhibitor : Dust binding agent : Flame retardant or fire preventing agent; Flotation agent; Stabiliser;

Viscosity control agent

Uses advised against None known.

1.3 Details of the supplier of the safety data sheet

PQ Corporation Company Identification

P.O. Box 840 Valley Forge PA 19482 USA

Telephone: +1 610-651-4200 E-Mail (competent person) sds.uk@pqcorp.com

1.4 Emergency telephone number

Emergency Phone No. +1 800-424-9300

# SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

**GHS Classification** Skin Irrit. 2

Eye Irrit. 2

**Hazards summary** Alkaline.

Irritating to eyes and skin. Spilled material is slippery

2.2 Label elements

Hazard pictogram(s)



Signal word(s) Warning

Hazard statement(s) H315: Causes skin irritation.

H319: Causes serious eye irritation.

Revision: GHS Ref: 02-3-2-25-000 - en -Date of Issue: 02/2023 PQUS - GHS - 3 Date Previous Issue: 04/2020

Page: 1 of 6





P262: Do not get in eyes, on skin, or on clothing. Precautionary statement(s)

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Dries to form glass film which can easily cut skin. Can etch glass 2.3 Other hazards

if not promptly removed.

#### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Regulation (EC) No. 1272/2008 (CLP)

Ingredient(s)	%W/W	CAS No.	EINECS No. /	Hazard symbol(s) and
			REACH Registration	hazard statement(s)
Silicic acid, sodium salt	37.5	1344-09-8	215-687-4	H315 : Skin Irrit. 2 ;
				H319 : Eye Irrit. 2
Water	62.5	7732-18-5	231-791-2	

#### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

**Eye Contact** Irrigate with eyewash solution or clean water, holding the eyelids

apart, for at least 15 minutes. Obtain immediate medical

attention.

Skin Contact Wash affected skin with plenty of water. If symptoms develop,

obtain medical attention.

Inhalation Remove patient from exposure, keep warm and at rest. Obtain

medical attention.

Ingestion Do not induce vomiting. Wash out mouth with water and give

200-300 ml (half a pint) of water to drink. Obtain medical

attention.

4.2 Most important symptoms and effects, both acute and

delaved

4.3 Indication of any immediate medical attention and special

treatment needed

Alkaline.

Irritating to eyes and skin. The toxicity of sodium silicate is

dependent on the silica to alkali ratio and on the pH.

Obtain immediate medical attention.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable Extinguishing Media Unsuitable extinguishing Media

None known.

5.2 Special hazards arising from

Not applicable. Aqueous solution. Non-combustible.

Compatible with all standard fire fighting techniques.

the substance or mixture 5.3 Advice for fire-fighters

None.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Wear eye/face protection.

Revision: GHS Ref: 02-3-2-25-000 - en -Date of Issue: 02/2023 PQUS - GHS - 3 Date Previous Issue: 04/2020 Page: 2 of 6





**6.2 Environmental precautions** Do not allow to enter drains, sewers or watercourses. Advise

Authorities if spillage has entered water course or sewer or has

contaminated soil or vegetation.

6.3 Methods and materials for containment and cleaning up

Caution - spillages may be slippery. Contain spillages with sand, earth or any suitable adsorbent material. Transfer to a container

for disposal or recovery.

**6.4 Reference to other sections** See Also Section 8.

### SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling** Avoid contact with eyes, skin and clothing.

Avoid generation of mist. Provide adequate ventilation. Emergency shower and eye wash facilities should be readily

available.

See Also Section 8

7.2 Conditions for safe storage, including any incompatibilities

Store at temperature below 60°C/140°F

Do not allow material to freeze. Provide an adequate bund wall.

Unsuitable containers: Aluminium See Also Section 10.

7.3 Specific end use(s)

See also Annex to the extended Safety Data Sheet.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

SUBSTANCE.	Occupational Exposure Limits		
Silicic acid, sodium salt	No Occupational Exposure Limit assigned.		
	An exposure limit of 2 mg/m3 (15 min TWA) is recommended by analogy		
	with sodium hydroxide (UK EH40).		

**8.2 Exposure controls**Wear protective equipment to comply with good occupational

8.2.1 Appropriate engineering

controls

hygiene practice. Do not eat, drink or smoke at the work place. Engineering methods to prevent or control exposure are preferred. Methods include process or personnel enclosure, mechanical ventilation (dilution and local exhaust), and control of

process conditions.

8.2.2 Personal Protection

Respiratory protection Respiratory protection not normally required. Advice on

respiratory protective equipment is given in the HSE (Health and

Safety Executive) publication HS(G)53.

Eye/face protection Chemical goggles (EN 166).

Skin protection Wear suitable protective clothing and gloves. Plastic or rubber

gloves. For example EN374-3, level 6 breakthrough time

(>480min). Wear suitable overalls.

8.2.3 Environmental Exposure

**Controls** 

The primary hazard of sodium silicate is the alkalinity. Avoid

release to the environment.

### **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

#### 9.1 Information on basic physical and chemical properties

Appearance Liquid. Almost colourless.

Odour
Odourless.
Odour Threshold (ppm)
PH (Value)
Freezing Point (°C)
Melting Point (°C)
Not applicable.
Not applicable.
Not applicable.

Boiling Point (°C) 100

Flash Point (°C) [Closed cup] Not applicable.

Revision: GHS v1 - en - Ref: 02-3-2-25-000

Date of Issue: 04/2020 PQUS - GHS - 3

Date Previous Issue: 01/2017 Page: 3 of 6





Evaporation rate Not applicable. Flammability (solid, gas) Not applicable. Explosive Limit Ranges Not applicable.

Vapour pressure (Pascal)

Vapour Density (Air=1) No data.

Density (g/ml) 1.39 g/cm3 (20°C), 41° Bé, 11.62 lbs/gal

Solubility (Water) Solubility (Other) No data. Partition Coefficient No data. Auto Ignition Point (°C) Not applicable. Decomposition Temperature (°C) Not applicable. Viscosity (mPa. s) Not applicable. Explosive properties Not applicable. Oxidising Properties Not applicable. 9.2 Other information No data.

### **SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity** See Section: 10.3

**10.2 Chemical stability** Stable.

10.3 Possibility of hazardous W

reactions

When arc welding vessels containing aqueous solutions of this material, take care to control any explosion risk from hydrogen

evolved by electrolysis. Aqueous solutions will react with

aluminium, zinc, tin and their alloys evolving hydrogen gas which can form an explosive mixture with air. Can react violently if in contact with acids. Can react with sugar residues to form carbon

monoxide.

10.4 Conditions to avoidSee Section: 10.310.5 Incompatible materialsSee Section: 10.310.6 Hazardous decompositionNone known.

product(s)

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

**Acute toxicity** 

Ingestion All symptoms of acute toxicity are due to high alkalinity. Material

will cause irritation. Oral LD50 (rat) 3400 mg/kg bw

Inhalation Mist is irritant to the respiratory tract. All symptoms of acute

toxicity are due to high alkalinity. Inhalation LC50 (rat) >2.06 g/m<sup>3</sup>

Skin Contact Material will cause irritation. Dermal LD50 (rat) >5000 mg/kg bw

Eve Contact Material will cause irritation.

Skin corrosion/irritation Irritating to skin.
Serious eye damage/irritation Irritating to eyes.
Sensitisation Not sensitising.

**Mutagenicity** No evidence of genotoxicity. In vitro/in vivo negative.

Carcinogenicity No structural alerts. IARC, NTP, OSHA, ACGIH do not list this

product or any components thereof as known or suspected

carcinogen.

**Reproductive toxicity**No evidence of reproductive toxicity or developmental toxicity.

STOT - single exposure Not classified

STOT - repeated exposure Not classified. NOAEL oral (rat) >159 mg/kg bw/d

Aspiration hazard Not classified

Other information

# SECTION 12: ECOLOGICAL INFORMATION

Revision: GHS - en - Ref: 02-3-2-25-000

Date of Issue : 02/2023 PQUS - GHS - 3

Date Previous Issue : 04/2020 Page: 4 of 6





Fish (Brachydanio rerio) LC50 (96 hour) 1108 mg/l 12.1 Toxicity

Aguatic invertebrates: (Daphnia magna) EC50 (48 hour) 1700

mg/l

12.2 Persistence and

degradability

Inorganic. Soluble silicates, upon dilution, rapidly depolymerise into molecular species indistinguishable from natural dissolved

Inorganic. The substance has no potential for bioaccumulation.

12.3 Bioaccumulative potential

12.4 Mobility in soil

12.5 Results of PBT and vPvB

assessment

Not classified as PBT or vPvB.

12.6 Other adverse effects The alkalinity of this material will have a local effect on

Not applicable.

ecosystems sensitive to changes in pH.

### SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Dispose of this material and its container to hazardous or special

waste collection point.

Disposal should be in accordance with local, state or national

legislation.

### SECTION 14: TRANSPORT INFORMATION

Not classified according to the United Nations 14.1 UN number

> 'Recommendations on the Transport of Dangerous Goods'. Not classified as hazardous under DOT or US Transport

Recommendations.

International Maritime Dangerous Goods (IMDG) Code: Not

classified as hazardous

Not applicable. 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Not applicable. 14.4 Packing group Not applicable.

Not classified as a Marine Pollutant. 14.5 Environmental hazards 14.6 Special precautions for user Unsuitable containers: Aluminium

14.7 Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code

Not applicable.

#### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

TSCA Inventory Status: Reported/Included. AICS Inventory Status: Reported/Included.

DSL/NDSL Inventory Status: Reported/Included. SARA TITLE III: Not an Extremely Hazardous Substance under §302. Not a Toxic Chemical under §313. Hazard

Categories under §§311/312: Acute

German Water Hazard Classification VwVwS: Product ID number 1314, WGK class 1 (low hazard to

HMIS (Hazardous Material Information System) 2,0,0

15.2 Chemical Safety Assessment Information available on request.

# **SECTION 16: OTHER INFORMATION**

Revision: GHS Ref: 02-3-2-25-000 - en -Date of Issue: 02/2023 PQUS - GHS - 3 Date Previous Issue: 04/2020 Page: 5 of 6





Data referenced in this eSDS is from company-owned information and from data legitimately accessed by PQ Corporation through membership of Industry Consortia or other agreements. This includes data relating to toxicology, ecotoxicology, DNELs, PNECs and other information in this eSDS and its annex.

This SDS was last reviewed: 04/2020

The following sections contain revisions or new statements: All sections.

**GHS** Classification

Signal word(s) Hazard pictogram(s) Skin Irrit. 2

Eye Irrit. 2 Warning



Hazard statement(s) H315: Causes skin irritation.

H319: Causes serious eve irritation.

Precautionary statement(s)

P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves/protective clothing/eye

protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. PQ Corporation gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. PQ Corporation accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.